

MATERIAL SAFETY DATA SHEET

NAME: EL MARKO PERMANENT MARKER (FLAIR)

CAS NO: NA

Effective Date: March 29, 1984

A. - IDENTIFICATION

Composition*	%	Formula: NA
		Molecular Weight: NA
		Synonyms
		El Marko Permanent Marker - Black

B. - PHYSICAL DATA

Boiling Point 207 °F 97 °C	Melting Point -197 °F -127 °C	Freezing Point NA °F NA °C
Specific Gravity (H ₂ O=1) 0.8	Vapor Density (air=1) 2.1	Vapor Pressure @ (28°C) 77 °F 20.8 mmHg
Evaporation (Butyl Acetate =1) 1.3	Saturation in Air (by volume @ (25°C) 77 °F) 2.75 %	Autoignition Temperature 824 °F 440 °C
% Volatiles (by volume) NA	Solubility in Water Complete	pH NA

Appearance/Odor Liquid with alcoholic odor

Flash Point and 59°F (CC)
Test Method(s) 25°F (OC)Flammable Limits in Air
(% by volume) Lower 2.1 % Upper 13.5 %

C. - REACTIVITY

Stability	Conditions to Avoid	Polymerization	Conditions to Avoid
stable X	NA	may occur	NA
unstable		will not occur X	
Incompatible Materials	NA	Hazardous Decomposition Products	NA

*IF MULTIPLE INGREDIENTS INCLUDE CAS NUMBERS FOR EACH

NA=NOT AVAILABLE

Footnotes: Physical Data given for 1-Propanol

D - HEALTH HAZARD DATA**Occupational Exposure Limits (PELS, TLVS, etc.)**

None established for product. 8 hr. TWA for 1-Propanol is 200 ppm (OSHA, ACGIH).
(Skin notation).

Warning Signals

NA

Routes/Effects of Exposure**1. Inhalation**

None anticipated under normal use conditions.

2. Ingestion

None anticipated under normal use conditions. If misused, as sucking tip end of marker for extended period of time, some irritation/discomfort may occur.

3. Skin**a. Contact**

Contact will dye skin.

b. Absorption

None anticipated under normal use conditions. If large amounts of product come in contact with skin possibility of absorption may exist but not in toxic amounts.

4. Eye Contact

None under normal use conditions. If product contacts eye can expect some conjunctival/corneal irritation.

5. Other

NA

E - ENVIRONMENTAL IMPACT**1. Applicable Regulations****2. DOT Hazard Class --**

NA

3. DOT Shipping Name --**Environmental Effects**

NA

F - EXPOSURE CONTROL MEASURES

Engineering Controls

OT 0035

None under normal use conditions.

Eye Protection

None under normal use conditions.

Skin Protection

None under normal use conditions.

Respiratory Protection

None under normal use conditions.

Other

Product is considered safe when used under normal use conditions.

G - WORK PRACTICES

Handling and Storage

Keep cap on marker to prevent solvent evaporation.

Normal Clean Up

Wipe up with tissue, towel, etc. and discard with trash.

Waste Disposal Methods

Dispose as trash.

EMERGENCY PROCEDURES

Steps to be taken if material is released to the environment or spilled in the work area

Not applicable

Fire and Explosion Hazard

Flammable. If large amounts are involved plastic may also give off hazardous decomposition products.

Extinguishing Media

CO₂, Foam, Dry Chemical

Firefighting Procedures

If large amounts of product are involved use self-contained breathing apparatus and other protective gear.

I. - FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Eyes

Flush eyes immediately with water for at least five minutes. If irritation persists consult physician.

Skin

Wash with soap and water. Ink stain will eventually wear off.

Inhalation

None for normal use conditions.

Ingestion

Wash mouth out with water. Consult physician if irritation/discomfort persists.

Notes to Physician

NA

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.